

Auburn University 2019 Truck Bid Specifications

Model: 2020 International MV607 SBA w/ Lyncoach 26' L x 96" H x 96" W van body with Maxon 3000lb lift

Standard configuration, with
Calc. geared speed at min. 88.8MPH
Automatic 6-speed transmission
Two fuel tanks
Color: Winter White

Body:

26' L x 96" H x 96" W Inside Dimensions: 25' 10" L x 96 ½" H x 90 ¼" W
Radius Front (.063 Aluminum Tread Bright)
.032 Seamless Roof Skin Riveted Around Perimeter
1" Anti-Sag Roof Bows On 24" Centers
Clearance Lights - Trucklite (LED) Flex Lights with S/T/T on Outers Corners of Rear Roof Rail
Includes Lyncoach Plug & Play Wiring Harness (Molded Ends & Wrapped With Conduit)
LED Dome Light With Switch At Left Rear Side
.040 Pre Painted White Alum. Sides With Rivets On 2" Centers
Extruded Aluminum Z-Post On 16" Centers
1/2" Exterior Plywood Lining On Front Wall
3/8" Exterior Plywood Lining On Side Walls
40 Rope Ties (D-Rings)
20 Per Side, Evenly Spaced
1 1/8" Hardwood Floor (Undercoated)
3" I-Beam Crossmembers on 12" Centers (Hot Dipped For Corrosion Protection)
4" I-Beam Longitudinals
Reinforced Above Rear Wheels With 3/16" Steel
Stainless Steel Rear-End (Designed With Flush Entry)
Grab Handles On Rear
Composite Roll-Up Rear Door
Maxon GPT-3 3,000lb Tuk-A-Way Lift Gate - 60"x80" Aluminum Platform